

## Smootharc TIG 185 ACDC



The Smootharc TIG 185 ACDC machine is an inverter-based machine with added MMA welding capability. It delivers smooth arc characteristics that will assist you to complete high quality welds.

Ideal for all materials, its variable balance control means you can select the amount of cleaning or penetration required for aluminium welds. Its pulse capability allows you to control heat input when working on thin materials and its simplistic control panel makes it easy to use. Ideal for sheet metals, stainless steel and aluminium fabrications. Suits light industrial, maintenance and DIY jobs.

An optional foot control is also available (sold separately) to regulate current while welding.





## Specifications

| Part No.  |     | BOC185ACDC/FC                   |          |  |
|---|-----|---------------------------------|----------|--|
| Input voltage   |     | Single phase AC 240 V ±15%      |          |  |
| Frequency   |     | 50/60 Hz                        |          |  |
| Rated input   |     | 15                              |          |  |
|   |     | TIG                             | MMA      |  |
| Maximum rated input current (/ <sub>1max</sub> )      |     | 22.0 A                          | 24.5 A   |  |
| Maximum effective supply current (I <sub>1eff</sub> ) |     | 10.7A                           | 13.2 A   |  |
| Output range  |     | 10-180 A                        | 10-135 A |  |
| Rated working voltage                                 |     | 17.2 V                          | 25.4 V   |  |
| No-load voltage                                       |     | 64 V                            |          |  |
| Duty cycle  | 30% | 180 A                           | -        |  |
|   | 35% | -                               | 135 A    |  |
|   | 60% | 127 A                           | 104 A    |  |
| Arc initiation  |     | HF                              |          |  |
| Remote control  |     | Yes (foot control compatible)   |          |  |
| Efficiency  |     | 80%                             |          |  |
| Power factor  |     | 0.73                            |          |  |
| Insulation grade                                      |     | F                               |          |  |
| Housing protection grade                              |     | IP21                            |          |  |
| Weight  |     | 14.7 kg                         |          |  |
| Dimensions (L×W×H)                                    |     | 450×204×368 mm                  |          |  |
| Standards   |     | AS/NZS 60974-1, IEC/EN 60974-10 |          |  |

## Service and warranty 18 month warranty covers parts and labour. Excludes torches and consumable items. Warranty will not apply if operating and service instructions are not followed.

| Package includes | • | Power source                   |
|------------------|---|--------------------------------|
|                  | · | Work return lead               |
|                  | · | TIG Torch                      |
|                  | · | MMA electrode holder and cable |
|                  | • | Regulator                      |
|                  | • | Gas hose                       |
|                  | · | Operator's manual              |
|                  |   |                                |
|                  |   |                                |

Package excludes · Optional foot control (N-R021014) - sold separately

BOC Limited

ABN 95 000 029 729, 10 Julius Avenue, North Ryde NSW 2113, Australia, 131 262, www.boc.com.au WN007748, 970–988 Great South Road, Penrose, Auckland, New Zealand, 0800 111 333, www.boc.co.nz